

PSC SOLAR INDUSTRIES


+234 812 085 5444 or +(234)-808 955 2800 or email:info@pscsolaruk.com 41B OLUTOYE CRES. OFF ADENIYI JONES. IKEJA LAGOS


APP Control

Compatible With Multiple Systems More Convenient More Fashionable









The charging efficiency of MPPT controller is up to 10%-15% higher than that of non-mppt controller

Quality Assurance



We provide 5 years of warranty since the date of inspection

Item No.	Photo	Features & Specifications EXW Unit Price					
IN-280C-80W Slide Mounting		Rated LED Power	80W, Bridgelux LED, 2800-6500K CCT available Lumens:10400-12000LM Light Distribution: Batwing Type II	1-49(pcs)	50-99(pcs)	100-199(pcs)	200-500 (pcs)
		Solar Panel Capacity	18V 90W High Efficiency Monocrystalline more than 25 years warranty				
		Battery Capacity	Li-ion power battery 12V 50AH, 5 to 8 years lifespan	Mobile APP Remote Control - Switch the luminaire on and off remotely. - View the technical characteristics such as: Operating hours, battery voltage and temperature, solar panel voltage, etc - Identify malfunctions. Packing Details: 1. Carton size: 1345x500x185mm 2. N.W: 20kg/G.W: 22.5kg 3. Qty: 1pc/carton 4. 20GP: 220 Sets Applications: Public Square/Plaza/Courtyard/Garden/Park/ Street/ Roadway/ Pathway/Parking Lot/Private/Road/ Sidewalk/Campus/ Airfield /Farm &Ranch /Perimeter Security/Wildlife Area/Military Base			
		MAX Sensing Distance	12M				
		Solar Controller	Intelligent MPPT patent controller High conversion efficiency 91%				
		Light Body	Aluminum Alloy+Toughened Glass+Acrylic				
		Installation Height	8 to 10 meters				
		Distance between Pole	24 to 30 meters				
		Solar Charging Time	6 to 7 hours by bright sunlight				
		Operating Temperature	-25° to 65°				
		Product Size	1210x450x45mm				
		Protection Grade	IP65	and so on.			

Remark:

- 1. Above is EXW price without shipping charge and tax fee
- 2. Payment terms: Full payment before shipping with T/T, Western Union/Paypal, L/C
- 3. Warranty: 5 years for above items
- 4. Certificates: all our lamps approved with CE ROHS IP65 IES IEC ISO standards
- 5. All quotation exclude pole